SALLI SWING

Thanks to the swing mechanism, you can train all day without even noticing with Salli Swing! The seat has a fixed width.

The seat follows the body's movements, and different forward and side bends work like Pilates exercises, strengthening the lower back, pelvic area, and abdominal muscles. The chair that follows the movement helps maintain the natural curve of the back even in work tasks that involve leaning forward.

SEAT

- Two-part active seat
- 3 mm steel sheet seat plate
- · Leather, artificial leather, ESD artificial leather, or wool



| GAS SPRINGS | User height (cm) | Chair height Gas spring (mm, min–max) | Chair height Gas spring with Top&Bottom (mm, min–max) |
|-------------|------------------|---------------------------------------|---|
| Short | <150 | 425-540 | 430-550 |
| Medium | 150-170 | 515-695 | 540-725 |
| Long | >165 | 585-830 | 590-840 |

Mini gas spring is available for special circumstances; use depends on the working height, not on the height of the user.

Note! If you are using industrial or inline castors, the chair is 35 mm higher than the measurements shown in the table.

TECHNICAL FEATURES

- Weight 9.9 kg
- Height control by hand as a standard;
 Top & Bottom (foot height control)
 available
- Maximum load 120 kg
- Warranty 10 years



ACCESSORIES



Suitable For Salli Swing

ALLROUND

Allround moves freely on all sides of the chair, and also around its own axis. Can be used as a support for either one arm or both arms. Ø 600 mm base required.



TOB & BOTTOM

Enables height adjustment without using the lever by hand. Recommended for hygienic environments, such as operating theatres and dental clinics.



FOOT SUPPORT

A perfect accessory for high workstations to support the feet. Recommended for temporary use only. \varnothing 460 mm.

